

# SAFETY DATA SHEETS

## DECORATIVE TEXTURE MIX

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DECORATIVE TEXTURE MIX  
MANUFACTURER: Incredible Products LLC. ADDRESS: 1601 McKinley Rd. St. Mary's, OH 45885  
INFORMATION PHONE: 567-297-3700 EMERGENCY PHONE: 800-424-9300  
September 14, 2021

### SECTION 2: HAZARDOUS IDENTIFICATION

**Classification:**

Skin Irritation: Category 2  
Eye Irritation: Category 2B  
Respiratory Sensitizer (Solid/Liquid): Category 5  
Skin Sensitizer: Category 1  
Carcinogenicity: Category 2

**Signal Word:** Warning

**Hazardous Statements- Health:**

H320 - May cause eye irritation  
H315 - May cause skin irritation  
H317 - May cause an allergic skin reaction  
H333 - May be harmful if inhaled

**Precautionary Statements- General:**

P101 - If medical advice is needed, have the product label at hand  
P102 - Keep out of reach of children.  
P103 - Read label before use.

**Precautionary Statements- Prevention:**

P264 - Wash thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P261 - Avoid breathing dust  
P284 - <In case of inadequate ventilation> wear respiratory protection.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.

**Precautionary Statements- Response:**

P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice/attention.  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.  
P321 - Specific treatment (see section 4 on this SDS).  
P362 + P364 - Take off contaminated clothing. And wash it before reuse.  
P308 + P313 - IF exposed or concerned: Get medical advice/attention.

**Precautionary Statements- Storage:**

P405 - Store locked up.

**Precautionary Statements- Disposal:**

P501 - Dispose of contents/ container to an approved waste disposal plant.

### SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL
Portland Cement	65997-15-1	N/A	N/A	N/A
Silica Sand	14808-60-7	N/A	N/A	N/A

**SECTION 2 NOTES: \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.**

## SECTION 4: FIRST AID MEASURES

### **Inhalation:**

Remove the source of exposure or move the person to fresh air and keep them comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.

### **Skin Contact:**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Gently brush away excess product. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before re-use or discard. IF exposed or concerned: Get medical advice/attention.

### **Eye Contact:**

Remove the source of exposure or move the person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. Avoid direct contact. Wear chemical protective gloves, if necessary.

### **Ingestion:**

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Give 1 or 2 glasses of milk or water to drink and refer the person to medical personnel. Do not give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

## SECTION 5: FIRE FIGHTING MEASURES

### **SUITABLE EXTINGUISHING MEDIA:**

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

### **UNSUITABLE EXTINGUISHING MEDIA:**

If water is used, use very large quantities of cold water. The reaction between water and hot isocyanate may be vigorous. Water and foam may cause violent frothing and possibly endanger the life of the fire fighter.

### **Specific Hazards in Case of Fire:**

Exposure to vapors of heated isocyanates can be extremely dangerous

### **FIRE-FIGHTING PROCEDURES:**

Isolate immediate hazard areas and keep unauthorized personnel out. Move undamaged bags from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### **SPECIAL PROTECTIVE ACTIONS:**

Wear NIOSH approved self-contained breathing apparatus in positive pressure mode with a full-face piece. Boots, gloves (neoprene), goggles, and full protective clothing are also required. Care should always be exercised in dust/mist areas.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **Emergency Procedure:**

Keep unnecessary people away; isolate the hazard area and deny entry. Do not walk through spilled material. Dry material may be scooped up and placed in appropriate disposal containers.

### **Recommended Equipment:**

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### **Personal Precautions:**

Avoid breathing dust. Avoid contact with skin, eyes or clothing.

### **Environmental Precautions:**

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways.

## SECTION 7: HANDLING AND STORAGE

### GENERAL:

Wash hands after use.  
Do not get in eyes, on skin or on clothing.  
Do not breathe dust  
Use good personal hygiene practices.  
Eating, drinking and smoking in work areas is prohibited.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Eyewash stations and showers should be available in areas where this material is used and stored.  
Employee education and training in safe handling of this material is required under OSHA hazard communication standard. Individuals with existing respiratory diseases such as chronic bronchitis, emphysema, or asthma should not be exposed to isocyanates.

### VENTILATION REQUIREMENTS:

Use only with adequate ventilation to control air contaminants to their exposure limits.  
The use of local ventilation is recommended to control emissions near the source

### STORAGE ROOM REQUIREMENTS:

Store in cool, dry, well-ventilated areas away from strong oxidizers and any incompatibilities. Protect against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Case No	Ingredient	WT%	IDLH	Type	OSHA PEL	NIOSH PEL	ACGIH
14808-60-7	Sand, Crystalline Silica (Quartz)	30-40	50	Respirable fraction Total dust	10mg/m <sup>3</sup> + (%SiO <sub>2</sub> + 2) 30mg/m <sup>3</sup> + (%SiO <sub>2</sub> + 2)	0.05mg/m <sup>3</sup>	0.025mg/m <sup>3</sup> NE(f)
65997-15-1	Portland Cement	5-10		Respirable fraction Total dust	5mg/m <sup>3</sup> 15mg/m <sup>3</sup>	5mg/m <sup>3</sup> 10mg/m <sup>3</sup>	10mg/m <sup>3</sup> NE

### EYE PROTECTION:

Wear eye protection with side shields or goggles. If additional protection is needed for the entire face, use it in combination with a face shield.

### SKIN PROTECTION:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### RESPIRATORY PROTECTION:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect workers, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. When airborne concentrations exceed or are expected to exceed the TLV, use MSHA/NIOSH approved positive pressure supplied air respirator with a full-face piece or an air supplied hood. For emergencies, use a positive pressure self-contained breathing apparatus. Air purifying (cartridge type) respirators are not approved for protection against isocyanates.

### APPROPRIATE ENGINEERING CONTROLS:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**SPECIFIC GRAVITY:** N/A  
**BOILING POINT:** N/A  
**EVAPORATION RATE:** N/A  
**VAPOR DENSITY:** N/A  
**SOLUBILITY IN H<sub>2</sub>O:** DISPERSES

## SECTION 10: STABILITY AND REACTIVITY

**STABILITY:**

Stable

**CONDITIONS TO AVOID:**

Heat, high temperature, open flame, sparks, and moisture.

**HAZARDOUS REACTIONS/POLYMERIZATION:**

None known.

**INCOMPATIBLE MATERIALS:**

Do not mix with acids.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

None known.

## SECTION 11: TOXICOLOGICAL INFORMATION

N/A

## SECTION 12: ECOLOGICAL INFORMATION

N/A

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal:**

Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14: TRANSPORTATION INFORMATION

**U.S. DOT Information:**

Not regulated

**IMDG Information:**

Not regulated

**IATA Information:**

Not regulated

## SECTION 15: REGULATORY INFORMATION

N/A

## SECTION 16: OTHER INFORMATION

**DISCLAIMER:**

The information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.