

SAFETY DATA SHEETS

SAMSON 2618-TD

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WARRIOR SAMSOM 2618- TD
MANUFACTURER: Incredible Products LLC. ADDRESS: 1101 Lincoln Ave, Wapakoneta, OH 45895
INFORMATION PHONE: 567-297-3700 EMERGENCY PHONE: 800-424-9300
November 6, 2020

SECTION 2: HAZARDOUS IDENTIFICATION

Classification:

Skin Irritation: N/A
Eye Irritation: N/A
Respiratory Sensitizer (Solid/Liquid): N/A
Skin Sensitizer: N/A
Carcinogenicity: N/A

Hazardous Statements- Health:

The exhaust fumes from this machine contain toxic carbon monoxide gas, which can cause shortness of breath, or even death. Avoid breathing fumes and always have proper ventilation. Hearing and eye protection must be worn at all times.

Precautionary Statements- General:

P102- Keep out of reach of children
P103- Read Owner's Manual before use

Precautionary Statements- Prevention:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood

Precautionary Statements- Response:

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.

Precautionary Statements- Storage:

P405 - Store locked up.

Precautionary Statements- Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

N/A

SECTION 4: FIRST AID MEASURES

Inhalation:

Remove the source of exposure or move the person to fresh air and keep them comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.

Skin Contact:

IF exposed or concerned: Get medical advice/attention.

Eye Contact:

Remove the source of exposure or move the person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes.

Ingestion:

N/A

SAMSON 2618-TD

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

Dry chemical, foam, carbon dioxide or fog is recommended. Sand or earth may be used for small fires only.

UNSUITABLE EXTINGUISHING MEDIA:

N/A

Specific Hazards in Case of Fire:

Electric Shock

FIRE-FIGHTING PROCEDURES:

Isolate immediate hazard areas and keep unauthorized personnel out. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SPECIAL PROTECTIVE ACTIONS:

Wear NIOSH approved self-contained breathing apparatus in positive pressure mode with a full-face piece. Boots, gloves (neoprene), goggles, and full protective clothing are also required. Care should always be exercised in dust/mist areas.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

N/A

Recommended Equipment:

N/A

Personal Precautions:

N/A

Environmental Precautions:

N/A

SECTION 7: HANDLING AND STORAGE

GENERAL:

Wash hands after use.
Do not breathe vapors or mists.
Use good personal hygiene practices.
Eating, drinking and smoking in work areas is prohibited.

VENTILATION REQUIREMENTS:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

STORAGE ROOM REQUIREMENTS:

Store in cool, dry, well-ventilated areas.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION:

Wear eye protection with side shields or goggles. If additional protection is needed for the entire face, use it in combination with a face shield. Operators must tie back long hair, and not wear loose clothing or jewelry including rings. There is a risk of injury through items getting caught, or being drawn into moving machinery.

SKIN PROTECTION:

Use of gloves approved to relevant standards.

RESPIRATORY PROTECTION:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect workers, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. When airborne concentrations exceed or are expected to exceed the TLV, use MSHA/NIOSH approved positive pressure supplied air respirator with a full-face piece or an air supplied hood. For emergencies, use a positive pressure self-contained breathing apparatus.

APPROPRIATE ENGINEERING CONTROLS:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

WORKING AREA: 26.18"
MACHINE WEIGHT: 919 LBS.
VOLTAGE: 220V
PHASE: 1 & 3 PHASE
HORSEPOWER: 10 HP
HEAD PRESSURE: 264-440 LBS.
INVERTER: 15 KW
RPM/ROTATION: 0-700

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

This product is stable

CONDITIONS TO AVOID:

N/A

HAZARDOUS REACTIONS/POLYMERIZATION:

Will not occur under normal conditions.

INCOMPATIBLE MATERIALS:

N/A

HAZARDOUS DECOMPOSITION PRODUCTS:

N/A

SECTION 11: TOXICOLOGICAL INFORMATION

N/A

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal:

All packaging and batteries should be recycled according to applicable government regulations.

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT Information:

Not regulated

IMDG Information:

Not regulated

IATA Information:

Not regulated

SECTION 15: REGULATORY INFORMATION

N/A

SECTION 16: OTHER INFORMATION

DISCLAIMER:

The information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.