



# TECHNICAL DATA SHEET

# AMERIPOLISH SR2

## PRODUCT DESCRIPTION

The Concrete Protector's Ameripolish® SR2™ is a penetrating stain repellent specifically formulated to protect polished, dyed and non-dyed concrete from oil and water-based stains.

**STANDARD COLORS:** Clear

**OTHER COLORS ALSO AVAILABLE:** N/A

**REVISION DATE:** August 4, 2022

## CURE SCHEDULE (75°)

**POT LIFE (1.5 GAL VOLUME):** N/A

**TACK FREE (DRY TO TOUCH):** N/A

**RECOAT OR TOPCOAT:** N/A

**LIGHT FOOT TRAFFIC:** 1 hour

**FULL CURE:** 7 days

## COVERAGE

Recommended for use on new or existing polished concrete or exposed concrete flooring.

**COVERAGE PER GALLON:** 3,000 - 5,000 sq. ft.

**MIX RATIO:** N/A

**RECOMMENDED FILM THICKNESS:** N/A

**PACKAGING INFORMATION:** 1 gallon

## PHYSICAL PROPERTIES

**DENSITY:** N/A

**COLOR:** Clear

**VAPOR PRESSURE:** N/A

**SHELF LIFE:** 1 year

**PH LEVEL:** N/A

**EVAPORATION RATE:** N/A

**VOLATILE ORGANIC CONTENT:** Compliant (5g/l)

## CHEMICAL RESISTANCE

N/A

## LIMITATIONS

- Recommended for use with Ameripolish® 3D HS or HSL Densifiers
- Do not apply over 90°F (32°C); avoid application on hot, windy days
- Keep product from freezing
- Do not mix with other chemicals

## BENEFITS

- Safe for surfaces that experience high traffic
- VOC exempt & non-flammable
- Oil and food stain resistance
- Non-topical, penetrating sealer
- Long-lasting protection
- High coverage rate-
- Provides a chance to clean up spills before they stain or etch a surface
- Extreme hydrophobic and oleophobic characteristics for maximum stain resistance
- Compatibility to bond with Ameripolish Color System components to protect color in slab
- Few instances of color change (slightly darkens concrete)
- Excellent stain repellency for residential, commercial, and even industrial applications
- Treated surfaces 'breathe' and do not trap moisture



# TECHNICAL DATA SHEET

## AMERIPOLISH SR2

### INSTRUCTIONS

- 1) Spray a light mist of SR2TM onto concrete surface and immediately spread evenly with a microfiber pad.
- 2) Mop out any puddles thoroughly until they completely penetrate the surface.
- 3) Burnish with a high-speed burnisher, fitted with a 3000 grit or finer diamond-impregnated pad, or auto-scrub with white pad to remove surface haze.

### NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM

AMERIPOLISH SR2