



TECHNICAL DATA SHEET

DECORATIVE TEXTURE MIX

PRODUCT DESCRIPTION

The Concrete Protector Texture Mix is the most user-friendly, polymer modified, cementitious product in the industry with unmatched adhesion when combined with our High Density Resin.

STANDARD COLORS: WHITE
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: September 14, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): 15-60 min

TACK FREE (DRY TO TOUCH): 1-12 hours

RECOAT OR TOPCOAT: 1-12 hours

LIGHT FOOT TRAFFIC: 12-24 hours

FULL CURE: 28 days

COVERAGE

Recommended for refinishing damaged and worn concrete flatwork. Walkways, driveways, and parking decks.

COVERAGE PER BAG: 150-250 sq. ft.

MIX RATIO: 9qts-7qts high density resin per bag

RECOMMENDED FILM THICKNESS: 1/16" - 1/8"

PACKAGING INFORMATION: 50 lb. bag

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: 1500 psi 28 day 850 psi 7 day
COMPRESSIVE STRENGTH: 6100 psi 28 day 3750 psi 7 day
TENSILE STRENGTH: 890 psi 28 day 560 psi 7 day
ADHESION: Excellent
VISCOSITY: N/A
ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: N/A
SHELF LIFE: 1 year in unopened bags

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Not intended to be applied in thick coats
- Avoid using in temperatures below 50°
- Avoid using in temperatures above 85°
- Avoid filling expansion or control joints

BENEFITS

- High bond strength.
- High resistance to weather and freeze thaw cycles.
- Slip/skid resistance.
- Extremely durable and suited to vehicular traffic.



TECHNICAL DATA SHEET

DECORATIVE TEXTURE MIX

INSTRUCTIONS

- 1) Combine Texture mix with High Density Resin
- 2) Mix thoroughly with drill and drill paddle
- 3) *Optional...Add mineral pigment coloring
- 4) Apply to surface using a spray gun or metal/ magic trowel

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM