

PRODUCT DESCRIPTION

Easy Cove Adhesive is a multi-purpose gun grade 100% solids epoxy adhesive and repair paste. It is specially formulated for fast-track repairs and as an excellent adhesive for flooring accessory installations

STANDARD COLORS: Gray OTHER COLORS ALSO AVAILABLE: N/A MARCH 12, 2021

CURE SCHEDULE (75°)

TACK FREE (DRY TO TOUCH): 30-45 min

LIGHT FOOT TRAFFIC: N/A

RECOAT OR TOPCOAT: 30-45 min

FULL CURE: 45-60 min

POT LIFE (1.5 GAL VOLUME): N/A

COVERAGE Recommended to secure Easy Cove

commended to secure easy cove

COVERAGE: Approximately 20 linear feet per 300ml x 300 ml tube set

MIXED RATIIO: 1:1

RECOMMENDED FILM THICKNESS: 1%"- 14"

PACKAGING INFORMATION: 300ml dual cartridge kit

PHYSICAL PROPERTIES

VOLUME MIX RATION: 1:1

VISCOSITY (MIXED): 50,000 cps (approx.) SOLIDS CONTENT (%): 100% solids VOLATILE ORGANIC CONTENT: VOC/HAPs compliant APPLICATION TEMPS: 50°F - 80°F HARDNESS (ASTM D-2240): 85 (Shore D) GEL TIME: 15 minutes DRY TO TOUCH (RECOAT WITH COMPATIBLE PRODUCT): 30 minutes THROUGH CURE (ABLE TO SAND): 45minutes

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Do not thin this product
- Do not apply when humidity exceeds 70% indoors
- Allow each coat to dry to 'tack-free' prior to recoat
- When re-coating, always apply the next coat within 24 hours of completing the previous coat
- Relatively thin beads (¼" width x depth) are best avoid deep fill repairs in a single lift as minor cracking during cure may result
- Mix thoroughly until a uniform gray color is achieved
- Tube Set applicator works best when material is above 65F



EASY COVE ADHESIVE

BENEFITS

- Partially used tube seta can be capped and stored for later use
 - VOC compliant
- Non-shrink
- Easy application
- Good working time, but fast cure time
- High bond strength and tensile strength

INSTRUCTIONS

1) Apply using dual cartridge 300ml x 300ml industrial caulk gun

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANT IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM