



TECHNICAL DATA SHEET

FLEXKRETE FLEXSEAL WB SEALER

PRODUCT DESCRIPTION

FlexKrete FlexSeal WB Sealer is a water based, aliphatic, acrylic polyurethane sealer used as a final seal coat for broadcast systems

STANDARD COLORS: Semi-Clear
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: September 30, 2021

CURE SCHEDULE (75°)

- POT LIFE (1.5 GAL VOLUME):**
- TACK FREE (DRY TO TOUCH):**
- RECOAT OR TOPCOAT:**
- LIGHT FOOT TRAFFIC:**
- FULL CURE:**

COVERAGE

Recommended for use as a final seal coat for broadcast systems, to seal concrete floors and eliminate dusting, to enhance the color and provide gloss for stone, wood and masonry products, and as a clear sealer for epoxy stone and other decorative systems. Can be used on concrete wood, steel, stone, masonry and FlexKrete.

COVERAGE PER GALLON: 240 sq. ft

MIX RATIO: N/A

RECOMMENDED FILM THICKNESS: 3 mils

PACKAGING INFORMATION: : 5 gallon pails

PHYSICAL PROPERTIES

- 100% MODULUS:** >2800PSI
- PH (AS LIQUID):** 7.1-8.0
- TENSILE STRENGTH:** >5000PSI
- SOLIDS BY VOLUME:** 45%
- WEIGHT PER GALLON:** 8.8 LBS
- SOLVENT:** None
- ULTIMATE ELONGATION:** >200%
- SWARD HARDNESS:** 30
- VOLATILE ORGANIC CONTENT:** None
- SHELF LIFE:** 1 Year

CHEMICAL RESISTANCE

N/A

FLEXKRETE FLEXSEAL WB SEALER



TECHNICAL DATA SHEET

EPOXY PRIMER- CONDUCTIVE

LIMITATIONS

- Apply thin, do not puddle
- Must be stored at 40 degrees or above
- Existing coatings may either be removed or abraded
- -Must be applied at 45 degrees or above

BENEFITS

- Single Component
- Quick Drying
- Medium to High Gloss
- High Hardness
- Good Impact Resistance
- Excellent Adhesion
- Abrasion Resistance
- Excellent Flexibility
- Zero VOC
- Stable in Sunlight & Fluorescent

INSTRUCTIONS

- 1) Power mix, or invert and shake well before using.
- 2) Use good quality brush or roller; use single direction strokes with bristle brush, and crosshatch method with short nap roller. Can be sprayed with conventional or airless sprayer.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM