



TECHNICAL DATA SHEET

FLEXTEMP

PRODUCT DESCRIPTION

For use with FlexKrete Products, this accelerator can be added to speed up the curing process especially during cold temperature applications.

STANDARD COLORS: Clear

OTHER COLORS ALSO AVAILABLE: N/A

REVISION DATE: October 19, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A

TACK FREE (DRY TO TOUCH): N/A

RECOAT OR TOPCOAT: N/A

LIGHT FOOT TRAFFIC: N/A

FULL CURE: N/A

COVERAGE

Recommended for use with FlexKrete products to accelerate curing times.

COVERAGE PER GALLON: N/A

MIX RATIO TO FLEXKRETE: 1 gallon of FlexKrete (128 OZ.)—.75% X 128 oz.=.96 OZ—(1 oz.)

1/2 gallon of FlexKrete (64 oz.)—.75% x 64 oz. = .48 oz. (1/2 oz)

1 quart of FlexKrete (32 oz.) — .75% x 32 oz. = .24 oz (1/4 oz.)

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 5 oz. bottle

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A
COMPRESSIVE STRENGTH: N/A
TENSILE STRENGTH: N/A
ADHESION: N/A

VISCOSITY: N/A
ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: N/A
SHELF LIFE: N/A

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Must be mixed in after adding FlexKrete Catalyst
- Caution should be taken when using, so as to not attain a cure sooner than desired

BENEFITS

- Speeds up curing time of Flexkrete
- Aids in cold temperature applications of FlexKrete

FLEXTEMP



TECHNICAL DATA SHEET

FLEXTEMP

INSTRUCTIONS

1. Catalyze FlexKrete normally, using FlexKrete Catalyst
2. Mix in FlexTemp at rate of .5-- .1% of the FlexKrete

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM

FLEXTEMP