

FAST-SETTING RUBBER (FSR)

PRODUCT DESCRIPTION

Sani-Ted's Fast Setting Rubber (FSR) is a solvent free, high solids, super flexible coating. It can be applied to properly prepared substrates like concrete and is great for quartz broadcast for added abrasion resistance. It can be applied in temperatures below freezing

STANDARD COLORS: Gray
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: May 3, 2021

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL VOLUME): 8 mins

TACK FREE (DRY TO TOUCH): 4-6 hours

RECOAT OR TOPCOAT: 3-12 hours

LIGHT FOOT TRAFFIC: 6-10 hours

FULL CURE: 28 days

COVERAGE

Recommended for Vehicular Traffic Areas, Exterior and Interior High Traffic Pedestrian Surfaces, Commercial Decks and Balconies, Kennels and Interior Surfaces.

COVERAGE PER GALLON: 1 Gallon 50-110 Sq. Ft.

MIX RATIO: 4 Parts A to 1 Part B

RECOMMENDED FILM THICKNESS: 15+/- 1 Mils

PACKAGING INFORMATION: 5 gallon kit, 1 gallon kit

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A

COMPRESSIVE STRENGTH: N/A

TENSILE STRENGTH: 2450-2650 psi @ ASTM D638

ADHESION: N/A

VISCOSITY: Part A mixed with Part B= 1240- 2080 cps

ABRASION RESISTANCE: N/A

ULTIMATE ELONGATION: 900% - 1100%

HARDNESS: Shore A= 65 (+/-3)

VOLATILE ORGANIC CONTENT: 0.04lb/gal

SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Not UV Stable
- Do not dilute under any circumstances
- May turn cloudy due to moisture penetration
- Surface may be slippery when wet

BENEFITS

- Can be applied at any thickness
- Good thermal stability
- Non-Gassing
- Meets USDA criteria
- Excellent low temperature flexibility fast setting & rapid cure
- Application as low as 18°

FAST-SETTING RUBBER (FSR)

INSTRUCTIONS

- 1) Premix Part A and Part B separately
- 2) Combine 4 parts Part A with 1 part Part B and mix slowly for 1-1.5 min. until even color is obtained
- 3) Apply using a notched squeegee or trowel. Use a looped roller to avoid air entrapment

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM