



## TECHNICAL DATA SHEET

# GLOW IN THE DARK PIGMENT

### PRODUCT DESCRIPTION

The Concrete Protector's Glow-in-the-Dark Pigments absorb light and slowly emit a glow over time.

**STANDARD COLORS:** Crimson, Bright Yellow Green, Blue-Green

**OTHER COLORS ALSO AVAILABLE:** Crimson, Bright Yellow Green, Blue-Green  
MARCH 12, 2021

### CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A  
TACK FREE (DRY TO TOUCH): N/A  
RECOAT OR TOPCOAT: N/A  
LIGHT FOOT TRAFFIC: N/A  
FULL CURE: N/A

### COVERAGE

Recommended as an additive to resins, sealers, clear coats, and epoxies

**COVERAGE:** N/A

**MIXED RATIO:** 1-2 bottles per gallon of mixed material

**RECOMMENDED FILM THICKNESS:** N/A

**PACKAGING INFORMATION:** Packaged in an 8 oz. bottle

### PHYSICAL PROPERTIES

**ODOUR:** None

**ODOUR THRESHOLD:** Not applicable

**pH:** Not applicable

**MELTING POINT/FREEZING POINT:** No information available

**INITIAL BOILING POINT AND BOILING RANGE:** No information available

**FLASHPOINT:** >1050°C

**FLAMMABILITY (SOLID, GAS):** No information available

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** No information available

**VAPOUR PRESSURE:** No information available

**VAPOUR DENSITY:** No information available

**RELATIVE DENSITY:** 3.6g/cm<sup>3</sup>

**SOLUBILITY(IES):** Water solubility 300mg/l @ 20°C and pH 11.35

**PARTITION COEFFICIENT (N-OCTANOL/WATER):** Log Pow: 0 @ 20°C and pH 11.92 - 11.96

**AUTOIGNITION TEMPERATURE:** No information available

**DECOMPOSITION TEMPERATURE:** No information available

**VISCOSITY:** No information available

**EXPLOSIVE PROPERTIES:** No information available

**OXIDISING PROPERTIES:** Not oxidising

### CHEMICAL RESISTANCE

N/A

### LIMITATIONS

- Pre-mix into resin component of desired coating product to avoid streaking or comet trail effects



## TECHNICAL DATA SHEET

# GLOW IN THE DARK PIGMENT

### BENEFITS

- Original artistic design effects
- Easy field blending & installation
- Multi-dimensional color effects
- High temperature resistance
- Exceptional light fastness & weather resistance

### INSTRUCTIONS

- 1) Shake jar
- 2) Add appropriate amount to the resin component of clear coating
- 3) Mix thoroughly
- 4) Optional\* Let set for 12-24 hours for air release

### NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM