

# **HIGH NOON FLOOR FINISH**

## **PRODUCT DESCRIPTION**

The Concrete Protector's High Noon Floor Finish is a 20% solids acrylic floor finish which provides high gloss and good durability.

STANDARD COLORS: WHITE
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: April 15, 2021

## **CURE SCHEDULE (75°)**

POT LIFE (1.5 GAL VOLUME): N/A

TACK FREE (DRY TO TOUCH): 30-60 minutes

**RECOAT OR TOPCOAT:** 30-60 minutes **LIGHT FOOT TRAFFIC:** 30-60 minutes

FULL CURE: 24 hours

## **COVERAGE**

Recommended for use on resilient and hard surface floors where burnishing is applicable.

COVERAGE PER GALLON: 1,500-3,000 sq. ft

MIX RATIO: N/A

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 1 gallon

## PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A
COMPRESSIVE STRENGTH: N/A
TENSILE STRENGTH: 4000+/-200psi @ ASTM D-412
ADHESION: N/A
VISCOSITY: 2900 (+/-500) cps
SLIP RESISTANCE: 0.5 minimum (ASTM D2047)

ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: N/A
SHELF LIFE: 2 years in unopened containers

## **CHEMICAL RESISTANCE**

N/A

#### **LIMITATIONS**

- Floor will be very slippery until dry
- Temperature, humidity, and ventilation could affect dry time
- Not intended for use on rubber, cork, wood, or bamboo flooring

#### **BENEFITS**

- Ultra-durable finish allows for reduced labor costs by extending recoat and strip-out cycles
- Built with tough all-acrylic polymers
- Burnishes to a rich deep gloss
- Solids Content 20%
- Meets ASTM D-2047 slip resistance requirements

#### INSTRUCTIONS

- 1) Apply to floor using a clean mop
- 2) Apply additional coats until desired gloss is obtained sealer
- 3) Allow 30-45 minutes of drying time between coats
- 4) Allow finish to cure for 24 hours before burnishing

#### NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE IT FOR ANY DISTINCT PURPOSE. NO WARRANT IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM