

MATCH PATCH PRO RAPID SET GROUT POWDER

PRODUCT DESCRIPTION

The Concrete Protector's Match Patch Pro Rapid Set Grout Powder is a cement based pinhole grout filler for polished concrete floors.

STANDARD COLORS: White
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: December 27, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A

TACK FREE (DRY TO TOUCH): 2 hours

RECOAT OR TOPCOAT: 2- 12 hours

LIGHT FOOT TRAFFIC: 2 hours

FULL CURE: 24 hours

COVERAGE

Recommended for damaged concrete floors prior to the polishing process

COVERAGE PER SQ. FT.: 100 sq. ft. per pound

MIX RATIO: N/A

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 1 gallon

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A
COMPRESSIVE STRENGTH: 5,000 psi
TENSILE STRENGTH: 535 psi (concrete failure)
ADHESION: N/A
VISCOSITY: N/A
ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: Mohs Scale of Hardness 6+

VOLATILE ORGANIC CONTENT: N/A **SHELF LIFE:** 1 year in unopened containers

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Must store above 55°
- Must be at room temperature prior to use

BENEFITS

- Cure for polish in two hours
- Accepts concrete dyes
- Densifies with Reactive Silicates
- Does not shrink or crack
- Bonds tenaciously at critical repair edges and does not chip or break at the thinnest feather edges
- Can fill pin holes and cracks to ¼"



MATCH PATCH PRO RAPID SET GROUT POWDER

INSTRUCTIONS

- 1) Wet floor with water after #100 grit cut
- 2) Liberally broadcast grout onto floor
- 3) Spread dry grout evenly with broom
- 4) Moisten the grout using 50% water combined with 50% The Concrete Protector Hydrophobic
- Sealer, while using a grinding machine to run grout pans over wet grout
- 5) Let grout dry and spray densifier
- 6) Let dry completely (about 1 hour) and move forward with the polishing process

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL DBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE IT FOR ANY DISTINCT PURPOSE. NO WARRANT IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. URP RPODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM