



# TECHNICAL DATA SHEET

# PERMAFLEX ACCELERATOR

## PRODUCT DESCRIPTION

SaniTred's PermaFlex Accelerator is an additive added to PermaFlex and SuperThane to accelerate dry time.

**STANDARD COLORS:** Pale Yellow  
**OTHER COLORS ALSO AVAILABLE:** N/A  
MARCH 18, 2021

### CURE SCHEDULE (70°)

**POT LIFE (1.5 GAL VOLUME):** N/A  
**TACK FREE (DRY TO TOUCH):** N/A  
**RECOAT OR TOPCOAT:** N/A  
**LIGHT FOOT TRAFFIC:** N/A  
**FULL CURE:** N/A

### COVERAGE

Recommended as a drying accelerate for PermaFlex and SuperThane

**COVERAGE:** N/A

**MIXED RATIO:** 6.4 oz. per 1 gal. for slow set/  
12.8 oz. per gal. for fast set)

**RECOMMENDED FILM THICKNESS:** N/A

**PACKAGING INFORMATION:** 6.4 oz. bottle, 1 quart bottle

## PHYSICAL PROPERTIES

**SPECIFIC GRAVITY:** 0.867  
**PHYSICAL STATE:** Liquid  
**ODOR:** Amine like odor  
**SOLUBILITY:** Reacts slowly  
**VISCOSITY:** N/A  
**FLASH POINT:** 93 °C (200 °F)  
**BOILING POINT:** 200 °C (392 °F)  
**MELTING POINT:** N/A  
**DECOMPOSITION TEMPERATURE:** N/A  
**LEL:** N/A  
**VAPOR PRESSURE:** N/A  
**PH:** N/A  
**VOC%:** N/A  
**DENSITY LBS/GAL:** N/A  
**POUNDS PER CUBIC FOOT:** N/A  
**ODOR THRESHOLD:** N/A  
**PARTITION COEFFICIENT WATER/N-OCTANOL:** N/A  
**FLASH POINT METHOD:** TCC  
**BOILING RANG:** N/A  
**EVAPORATION RATE:** N/A  
**AUTO-IGNITION TEMPERATURE:** N/A  
**UEL:** N/A  
**VAPOR DENSITY:** Not Available  
**FLAMMABILITY:** N/A  
**PERCENT VOLATILE:** N/A

## CHEMICAL RESISTANCE

N/A

PERMAFLEX ACCELERATOR



## TECHNICAL DATA SHEET

# PERMAFLEX ACCELERATOR

### LIMITATIONS

- Additive for PermaFlex and SuperThane

### BENEFITS

- Can be used for slow set or fast set
- Can be used for PermaFlex and SuperThane

### INSTRUCTIONS

- 1) Combine correct measurements of PermaFlex or SuperThane and PermaFlex Accelerator (6.4 oz. per 1 gal. for slow set/ 12.8 oz. per gal. for fast set)
- 2) Mix until well blended

### NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM