



TECHNICAL DATA SHEET

PRESSURE WASHER

PRODUCT DESCRIPTION

The Honda GX390- 4,000PSI Pressure Washer is a professional grade, 4,000 psi, 4 gpm pressure washer powered by a reliable 390cc Honda GX390 gas engine

STANDARD COLORS: N/A

OTHER COLORS ALSO AVAILABLE: N/A

FEBRUARY 22, 2022

PHYSICAL PROPERTIES

ENGINE BRAND: Honda GX

HOSE LENGTH: 50 FT

HP: 13 HP

WEIGHT: 125 LBS

CC: 390 CC

LENGTH: 27 IN

FUEL TANK SIZE: 1.6 Gal.

WIDTH: 33 IN

WATER PRESSURE: 4,000 PSI

HEIGHT: 27 IN

WATER FLOW: 4 GPM

CHEMICAL RESISTANCE

N/A

LIMITATIONS

Operate pressure washer ONLY outdoors.

INSTRUCTIONS

MACHINE SET UP:

1. Place pressure washer near an outside water source capable of supplying water at a flow rate greater than 3.8 gallons per minute and no less than 20 PSI at pressure washer end of garden hose.
2. Make sure the unit is in a level position.
3. Connect garden hose to water inlet on pressure washer pump.
4. Attach wand extension to spray gun. Tighten by hand.
5. Choose desired spray tip, pull back nozzle extension collar, insert spray tip and release collar. Tug on spray tip to make sure it is securely in place.
6. Uncoil high pressure hose and attach the quick connect end of hose to the base of the spray gun. Pull down on the collar of the quick connect, slide onto the spray gun and let go of the collar. Tug on hose to be sure of tight connection.
7. Similarly, attach the other end of the high pressure hose to the high pressure outlet on the pump. Pull down on the collar or quick connect, slide onto the pump and let go of the collar. Pull on the hose to be sure of tight connection.
8. Turn Water Supply on, point the gun in a safe direction and squeeze the trigger to purge the pump of air and debris. Do this for at least 30 seconds.
9. Take a look at all connections to make sure there are no leaks or loose connections
10. Connect the garden hose to the water inlet. Tighten by hand.

MACHINE START UP:

1. To start the machine, locate the engine switch on the side of the engine, and switch it to the ON position. Check to ensure the fuel valve is in the ON position and, if starting cold, apply the choke.
2. Pull the recoil cord slowly until resistance is felt and then pull rapidly to avoid kickback. Make sure to position yourself in a balanced position.

MACHINE SHUT DOWN:

1. Release the spray gun trigger and let the engine idle down.
2. Turn the engine switch to the OFF position.
3. ALWAYS point spray gun in a safe direction, squeeze spray gun trigger to release retained high water pressure

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM.