



TECHNICAL DATA SHEET

PROTECTOR QUICK FIX

PRODUCT DESCRIPTION

The Concrete Protector's Quick Fix is a two component polymer concrete repair product used for small holes, pits and hairline cracking.

STANDARD COLORS: Gray
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: March 25, 2021

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL VOLUME): 1-4 min.

TACK FREE (DRY TO TOUCH): 10 min.

RECOAT OR TOPCOAT: 1 hour

LIGHT FOOT TRAFFIC: 10-20 min.

FULL CURE: 1 hour

COVERAGE

Recommended for repairing holes, cracks and uneven concrete slabs

COVERAGE PER KIT: : Variable

MIX RATIO: 1:1

RECOMMENDED FILM THICKNESS: Variable

PACKAGING INFORMATION: 2 Gallon Kit

PHYSICAL PROPERTIES

TENSILE STRENGTH: 4,300 psi

ADHESION: Excellent

VISCOSITY: Less than 25 cps

ABRASION RESISTANCE: Excellent

ULTIMATE ELONGATION: 4-6%

HARDNESS: 70

VOLATILE ORGANIC CONTENT: 6 grams per liter

SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- Work one small area at a time.
- Applying product to thick may cause product failure
- All new concrete must be cured for at least 30 days prior to application
- Substrate temperature must be 5 degrees F above dew point
- Not UV stable

BENEFITS

- Apply in thicknesses from 2 in. down to feather-finish
- Use for cracks in concrete slabs, driveways, or sidewalks
- Can also be used for broken steps, curbs, ramps, concrete overlays and large masonry cracks
- Sets in as little as 10 minutes
- High strength



TECHNICAL DATA SHEET

PROTECTOR QUICK FIX

INSTRUCTIONS

The product has a 1:1 liquid mix ratio by volume. Mix only an amount of material that can be used in 1-3 minutes.

- 1) Mix the liquids (1 part Part A and 1 part Part B) for 15 seconds
- 2) Add in the desired amount of CP Decorative Texture Mix to thicken and remix.
- 3) Immediately after the three components are mixed, (Product has a very short pot life), place the material into the area to be repaired with a trowel or other suitable equipment.
- 4) Trowel the floor to smooth out the area and remove any excess material.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM