



TECHNICAL DATA SHEET

SANI-TRED QUICK PATCH

PRODUCT DESCRIPTION

Sani-Tred Quick Patch is a fast curing, 2 component, low odor, liquid applied, polyurethane concrete repair material designed to repair concrete and other masonry substrates.

STANDARD COLORS: Grey
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: April 7, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): 80 seconds

TACK FREE (DRY TO TOUCH): 2-6 minutes

RECOAT OR TOPCOAT: 5-10 minutes

LIGHT FOOT TRAFFIC: 5-10 minutes

FULL CURE: 10 minutes

COVERAGE

Recommended for repairing holes or divots in concrete surfaces.

COVERAGE PER SQ. FT.: Coverage rates depend on size of hole or divot

MIX RATIO: 1 Part A to 1 Part B

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 1 Quart Kit, 2 Gallon Kit

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A

COMPRESSIVE STRENGTH: 4,750 psi@ ASTM C- 42

TENSILE STRENGTH: 2,200 +/- 200 psi@ ASTM D-412

ADHESION: Excellent

VISCOSITY: Part A= 80 +/- 20 cps Part B= 150 +/- 30 cps

ABRASION RESISTANCE: N/A

ULTIMATE ELONGATION: 4 +/- .05%@ ASTM D-412

HARDNESS: 70 +/- 5 Shore D@ ASTM D-2240

VOLATILE ORGANIC CONTENT: N/A

SHelf LIFE: 1 year

CHEMICAL RESISTANCE

QUICK PATCH WAS UNAFFECTED BY THE FOLLOWING CHEMICALS:

ACIDIC CHEMICALS

ACETIC ACID, 1%

ACETIC ACID, 10%

HYDROCHLORIC ACID, 1%

HYDROCHLORIC ACID, 10%

SULFURIC ACID 1%

SULFURIC ACID 10%

BASIC CHEMICALS

AMMONIUM HYDROXIDE, 1%

AMMONIUM HYDROXIDE, 10%

OILS, FUELS AND OTHER CHEMICALS

HYDRAULIC OIL

MOTOR OIL

OTHER COLORS ALSO AVAILABLE: N/A

UNLEADED GAS (REGULAR)

UNLEADED GAS (PREMIUM)

HEXANE

IPA

MIBK

XYLENE

SANI-TRED QUICK PATCH



TECHNICAL DATA SHEET

SANI-TRED QUICK PATCH

LIMITATIONS

- Opened container must be used as soon as possible
- Mix no more material than can be applied in 1 min.
- Must mix VIGOROUSLY

BENEFITS

- Non- Hazardous
- Resistant to most oils, solvents, and acids
- May be subjected to extreme cold during shipping with no ill effect
- Non-Toxic
- Solvent Free
- Low VOC
- Low Odor

INSTRUCTIONS

- 1) Premix Part A and Part B separately
- 2) Combine 1 part of Part A and 1 part of Part B
- 3) Mix vigorously
- 4) Optional* Add 1-3 parts of The Concrete Protector Decorative Texture Mix for thickening
- 5) Pour into holes or divots

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM