

STAIN GUARD

PRODUCT DESCRIPTION

The Concrete Protector's Stain Guard is a one component water based hydrophobic organic polymer designed specifically for use in the grind and polish of concrete/cement as a surface conditioner and stain guard.

STANDARD COLORS: Opaque milky white color OTHER COLORS ALSO AVAILABLE: N/A REVISION DATE: April 15, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): N/A
TACK FREE (DRY TO TOUCH): N/A

RECOAT OR TOPCOAT: : None required. Multiple

coats of this product are

compatible.

LIGHT FOOT TRAFFIC: N/A

FULL CURE: 24-48 Hours

COVERAGE

Recommended for use in the grind and polish of concrete/ cement as a surface conditioner and stain guard to be applied before the final polishing step to increase long term performance, gloss and stain resistance.

COVERAGE PER SQ. FT.: 800-1,200 sq. ft. per gallon

MIX RATIO: N/A

RECOMMENDED FILM THICKNESS: N/A

PACKAGING INFORMATION: 1 gallon pail, 5 gallon pail

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A
COMPRESSIVE STRENGTH: N/A
TENSILE STRENGTH: N/A
ADHESION: N/A
VISCOSITY: >25 cps
ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: 50/lt

SHELF LIFE: One year in unopened containers when stored between 50-80° Fahrenheit

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- The surface should be dry prior to the application of this product.
- This product is intended for interior use only.
- Always apply a test patch to determine the suitability before using.
- Allow to completely dry before polishing.
- · Product may slightly darken the substrate.
- Stain resistance and water repellency may not fully develop for 2-4 days.



STAIN GUARD

BENEFITS

- Increases durability, stain resistance and abrasion resistance.
- · Improves weathering, densifies and reduces efflorescence.
- Protects and fortifies concrete as it seals against moisture damage.
- Application will reduce dusting and increase concrete life.
- · Reduces water absorption into the substrate.

INSTRUCTIONS

- 1) Premix by stirring
- 2) Apply to surface with a pump-up sprayer and spread with a microfiber pad
- 3) Allow the material to completely dry before completing the final polishing step.
- 4) Keep the floor completely dry for at least 24 hours after the final polishing step is performed.

Product is intended for indoor application

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE IT FOR ANY DISTINCT PURPOSE. NO WARRANT IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM