



TECHNICAL DATA SHEET

STAMP MIX

PRODUCT DESCRIPTION

The Concrete Protector's Stamp Mix is a ready to use, one component overlay system that bonds to all clean concrete surfaces to produce a solid surface. This material can be troweled or stamped.

STANDARD COLORS: White Bag Mix
OTHER COLORS ALSO AVAILABLE: N/A
REVISION DATE: July 6, 2021

CURE SCHEDULE (75°)

POT LIFE (1.5 GAL VOLUME): 1-5 hours
TACK FREE (DRY TO TOUCH): 1-5 hours
RECOAT OR TOPCOAT: 1-5 hours
LIGHT FOOT TRAFFIC: 1-5 hours
FULL CURE: 28 days

COVERAGE

Recommended for refinishing damaged and worn concrete flatwork.
Walkways, driveways, and parking decks

COVERAGE PER BAG: 10-15 sq. ft. @ 3/8" /
20-25 sq. ft. @ 1/4"

MIX RATIO: 5 quarts of water per bag

RECOMMENDED FILM THICKNESS: 3/8" to 1/4"

PACKAGING INFORMATION: 50lb Bag

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: 2,450 psi
COMPRESSIVE STRENGTH: 5,200 psi
TENSILE STRENGTH: 920 psi
ADHESION: N/A
VISCOSITY: N/A
ABRASION RESISTANCE: 140.0mg (ASTM D-4060) CS-17 Disk, 1KG, 1000 Cycles
ULTIMATE ELONGATION: N/A
HARDNESS: Shore D Durometer 60
VOLATILE ORGANIC CONTENT: N/A
SHELF LIFE: N/A

CHEMICAL RESISTANCE

N/A

LIMITATIONS

- May reflect working cracks in substrate.
- May not be installed over working pour joints, control, or expansion joints and large moving cracks or cold joints
- Dry time is approximately 8 hours per 1/4" of thickness, and materials must not be exposed to temperatures below freezing during storage and initial curing period, low temperatures will increase dry time.
- Installation should not be attempted when temperatures are below 55°F (12°C) or above

BENEFITS

- One component mix. No extra additives. Just add water, mix and apply.
- For repairing and resurfacing old concrete.
- Rock hard surface.



TECHNICAL DATA SHEET

STAMP MIX

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM