

### PRODUCT DESCRIPTION

The Concrete Protector's WB 221 SATIN is a low sheen finish, two-component water based, 55% solids, aliphatic polyurethane.

**STANDARD COLOR:** CLEAR  
**OTHER COLORS AVAILABLE:** N/A  
**REVISION DATE:** March 25, 2022

### CURE SCHEDULE (75°)

**POT LIFE (1.5 GAL VOLUME) :** 45 MIN.  
**TACK FREE (DRY TO TOUCH):** 5-6 HOURS  
**RECOAT OR TOPCOAT:** 10-14 HOURS  
**LIGHT FOOT TRAFFIC:** 16-20 HOURS  
**FULL CURE:** 24 HOURS

### COVERAGE

Recommended for use as a topcoat on epoxy, concrete, plywood, and Graniflex™ Broadcast Systems

**COVERAGE PER GALLON:** 200-350 sq ft.  
**MIX RATIO:** 2 parts Part A to 1 part Part B  
**RECOMMENDED FILM THICKNESS:** 5-8 mils  
**PACKAGING INFORMATION:** 1.5 Gallon Kit

### PHYSICAL PROPERTIES

**FLEXURAL STRENGTH:** N/A      **VISCOSITY:** N/A      **VOLATILE ORGANIC CONTENT:** >100 grams/Liter  
**COMPRESSIVE STRENGTH:** N/A      **ABRASION RESISTANCE:** N/A      **SHELF LIFE:** 1 year in unopened container  
**TENSILE STRENGTH:** N/A      **ULTIMATE ELONGATION:** N/A  
**ADHESION:** N/A      **HARDNESS:** N/A

### CHEMICAL RESISTANCE

REAGENT	RATING
URINE	D
XYLENE	D
MEK	B
ISOPROPYL ALCOHOL	D
METHANOL	D
GASOLINE	D
SKYDROL	D
BRAKE FLUID	D
NITRIC ACID 10%	A
HYDROCHLORIC ACID 20%	D

RATING KEY: A - NOT RECOMMENDED, B - CONDITIONAL, C - RECOMMENDED CONDITIONAL, D - RECOMMENDED.

NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

### LIMITATIONS

- Will freeze during storage. Store at temps above 40F
- On grade slabs must perform a moisture-vapor transmission test.
- Clear coating may turn opaque and cloudy due to moisture penetration, especially exterior.
- Do not apply when substrate temperature is below 50 degrees or above 85 degrees
- Apply in thin coats
- Do not thin the product
- Do not apply less than 350 square foot per gallon or film properties will be impaired
- Not for use on brick
- Clear coating may turn opaque and cloudy due to moisture penetration, especially exterior.
- Do not apply when substrate temperature is below 50 degrees or above 85 degrees
- Apply in thin coats
- Do not thin the product
- Do not apply less than 350 square foot per gallon or film properties will be impaired
- Not for use on brick

## BENEFITS

- Easy to apply
- Low VOC
- Low odor
- Abrasion, chemical, and hot tire resistant

## INSTRUCTIONS

- 1) Premix Part A and Part B individually.
- 2) Measure out the desired amount needed.
- 3) Mix 1 Part B into 2 Part A and mix thoroughly for 3 minutes.
- 4) Apply to surface using a 3/8" nap roller

## NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM