



TECHNICAL DATA SHEET

WB-421 GLOSS

PRODUCT DESCRIPTION

Sanitred's WB 421 Gloss is a high gloss, 40% solids, two-component, water based, aliphatic polyurethane

STANDARD COLORS: CLEAR
OTHER COLORS ALSO AVAILABLE: N/A
MARCH 12, 2021

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL VOLUME): 45 minutes
TACK FREE (DRY TO TOUCH): 5-7 hours
RECOAT OR TOPCOAT: 6-12 hours
LIGHT FOOT TRAFFIC: 18-24 hours
FULL CURE: 5 days

COVERAGE

Recommended for use in clear epoxies and other clear products
COVERAGE PER GALLON: 300-500 sq. ft.
MIXED RATIO: 4 Parts A to 1 Part B
RECOMMENDED FILM THICKNESS: 5-10 mils
PACKAGING INFORMATION: 1.25 gallon kit

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: PASS
COMPRESSIVE STRENGTH: N/A
TENSILE STRENGTH: N/A
ADHESION: Concrete Failure
VISCOSITY: 200-300 cps
ABRASION RESISTANCE: 38-40 mg loss
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: < 100 grams/liter
SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

REAGENT	RATING	REAGENT	RATING
URINE	D	GASOLINE	D
XYLENE	D	SKYDROL	D
MEK	B	BRAKE FLUID	D
ISOPROPYL ALCOHOL	D	NITRIC ACID 10%	A
METHANOL	D	HYDROCHLORIC ACID 20%	D

LIMITATIONS

- Will freeze during storage
- Store at temps above 40F
- On grade slabs must perform a moisture-vapor transmission test.
- Clear coating may turn opaque and cloudy due to moisture penetration, especially exterior.
- Surfaces may be slippery when wet.
- Do not apply when substrate temperature is below 50 degrees or above 85 degrees
- Apply in thin coats
- Do not thin the product
- Do not apply less than 300 square foot per gallon or film properties will be impaired



TECHNICAL DATA SHEET

WB-421 GLOSS

BENEFITS

- Water based aliphatic urethane
- High gloss
- Low odor
- High chemical and wear resistance

INSTRUCTIONS

- 1) Combine a full kit of 4 Parts A to 1 Part B
- 2) Mix well with a slow speed mixer for 2-3 minutes.
- 3) Apply to surface using a magic trowel or 3/8" nap roller

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY:

The Concrete Protector (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM